



Sentinel

PROTECTIVE GLASS COATINGS

The clear choice for safer glass.

| | |
|--|----------------------------------|
| Product Code | AG04 |
| Film Colour (INT/EXT) | Clear Anti-Graffiti |
| Film Guage (metric/imp) | 100 micron/4.0mil |
| Film Roll Sizes | 72"/60"/48"/36"/24" |
| Adhesive Chemistry | Removable P.S. |
| Visible Light Transmitted (VLT) | 89% |
| Solar Energy Rejected (T.S.E.R.) | 18% |
| Shading Co-Efficient | 0.94 |
| Solar Energy Absorbed | 16% |
| Winter U-Value (W/M ² K) | 6.34 |
| Number of Film Plies | 1 |
| Tensile Strength at the Break (lbs/ins ² / kg/cm ²) | 28,000/2000 |
| Elongation at the Break | 125% |
| Peel Strength (gms/in / gms/cm) | 1600/640 |
| Break Strength (lbs/in) | 112 |
| AS2208 Tested on 3mm Glass | No |
| Ultra Violet Protection | 99% |
| Protection Factor Rating | UPF50+ |
| Warranty | 2 Years Outdoor / 4 Years Indoor |

Product specification performance data based on window film applied to 3mm (1/8") clear glass.
Published values are representative of typical production runs and are subject to normal manufacturing tolerances within industry standards.



automotive architectural protective specialty

Engineered for Australia...

AG04 CLEAR ANTI-GRAFFITI